



A Division of Thiessen Products, Inc.

INSTRUCTION SHEET FOR #2245



CLUTCH LOCK PLATE USE ON BIG TWIN 1941- EARLY 84

Use to lock clutch shell to clutch hub on all Big Twins, 1941- early 84.

CAUTION: Remove ground cable from battery.

1. Refer to H-D® Service Manual for removal of primary cover.
2. Disassemble clutch according to H-D® Service Manual.
3. Insert clutch lock plate between clutch hub and shell. Bend ears of lock washer away from hub nut, use JIMS® tool No.2316 Primary Locking Bar, to keep clutch housing from turning, remove clutch hub nut. **NOTE:** Clutch hub nut has left hand threads.

CAUTION: WEAR SAFETY GLASSES. EXCESSIVE FORCE MAY DAMAGE PARTS!
SEE JIMS® CATALOG FOR OVER 100 OTHER TOP QUALITY PROFESSIONAL TOOLS.
THE LAST TOOLS YOU WILL EVER NEED TO BUY.

555 DAWSON DRIVE, CAMARILLO, CA 93012 • PHONE 805-482-6913 • FAX 805-482-9224



A Division of Thiessen Products, Inc.

INSTRUCTION SHEET FOR #2245



CLUTCH LOCK PLATE USE ON BIG TWIN 1941- EARLY 84

Use to lock clutch shell to clutch hub on all Big Twins, 1941- early 84.

CAUTION: Remove ground cable from battery.

1. Refer to H-D® Service Manual for removal of primary cover.
2. Disassemble clutch according to H-D® Service Manual.
3. Insert clutch lock plate between clutch hub and shell. Bend ears of lock washer away from hub nut, use JIMS® tool No.2316 Primary Locking Bar, to keep clutch housing from turning, remove clutch hub nut. **NOTE:** Clutch hub nut has left hand threads.

CAUTION: WEAR SAFETY GLASSES. EXCESSIVE FORCE MAY DAMAGE PARTS!
SEE JIMS® CATALOG FOR OVER 100 OTHER TOP QUALITY PROFESSIONAL TOOLS.
THE LAST TOOLS YOU WILL EVER NEED TO BUY.

555 DAWSON DRIVE, CAMARILLO, CA 93012 • PHONE 805-482-6913 • FAX 805-482-9224